

Menüführung Expolite TourPAR Akku MKII (led51002)

ADDR	001 - 512			
STAT	R	0 - 255		
	G	0 - 255		
	B	0 - 255		
	A	0 - 255		
	W	0 - 255		
	UV	0 - 255		
	SHUT	0 - 255		
	PRSC	NON		
		R		
		G		
		B		
		A		
		W		
		UV		
		Yellow		
		Pink		
		Cyan		
		Orange		
		Violette		
		Golden		
2.700K				
3.200K				
4.000K				
5.500K				
6.500K				
RGBW				
SET	CAL	R	0 - 255	
		G	0 - 255	
		B	0 - 255	
		A	0 - 255	
		W	0 - 255	
		UV	0 - 255	
		USE	Yes/No	
	CHMD	12CH		
		9CH		
		7CH		
		6CH		
		5CH		
		4CH		
	DIM	LIN		
		SQR		
		ISQR		
		SCUR		
		LIN.		
		SQR.		
		ISQR.		
		SCUR.		
	DISY	On		
		2min		
	LOCK	Yes/No		
	BAT	High		
		MID		
		LOW		
SIGN	2.4G			
	CABL			
WIRE	REST	Yes/No		
	KEY			
CT01	R	0 - 255		
	G	0 - 255		
	B	0 - 255		

CTST	CT01	A	0 - 255	
		W	0 - 255	
		UV	0 - 255	
	.			
	.			
	.			
	CT10	R	0 - 255	
		G	0 - 255	
		B	0 - 255	
		A	0 - 255	
W		0 - 255		
UV		0 - 255		
AUTO	AT01	0 - 255		
	AT02	0 - 255		
	AT03	0 - 255		
	AT04	0 - 255		
	AT05	0 - 255		
	CHS1	RUN		
	CHS2	RUN		
CHS3	RUN			
PROG	SC01	R	0 - 255	
		G	0 - 255	
		B	0 - 255	
		A	0 - 255	
		W	0 - 255	
		UV	0 - 255	
		SHUT	0 - 255	
		AUTO	NONE/AT01-AT05	
		ATSP	0 - 255	
		TIME	0 - 255	
		WAIT	0 - 25.5	
		USE	Yes/No	
		.		
	CHS 1	SC20	R	0 - 255
			G	0 - 255
			B	0 - 255
			A	0 - 255
			W	0 - 255
			UV	0 - 255
			SHUT	0 - 255
			AUTO	NONE/AT01-AT05
			ATSP	0 - 255
			TIME	0 - 255
			WAIT	0 - 25.5
			USE	Yes/No
			.	
	.			
.				
CHS3	SC01	.		
.	.	.		
.	.	.		
.	.	.		
INFO	SOFT	Vx.x		
	POW	100%		
		80%		
		50%		
BAT	0-10			
LOAD	ST L	Yes/No		
	PR L	Yes/No		
SEND	Yes/No			