

EXPOLITE

Wireless Transmitter/Receiver



Manual


T ABLE OF CONTENTS

NOTES

PART 1 PRODUCT SPECIFICATIONS.....	1.
1.1-- <i>W-DMX PRODUCTS</i>	1.
1.2-- <i>PHYSICAL DIMENSIONS</i>	1.
PART 2 INSTALLATION.....	2.
2.1-- <i>TRANSMITTER</i>	2.
2.2-- <i>RECEIVER</i>	3.
2.3-- <i>POINT-TO-POINT OPERATION</i>	4.
2.3-- <i>POINT-TO-MULTIPOINT OPERATION</i>	4.


2.3 POINT-TO-POINT OPERATION

Point-to-point systems are used when you want to send wireless DMX data from a console to a single receiver. As the receiver accepts all 512 DMX channels from the transmitter you can easily daisy-chain more fixtures by cable from the original fixture that is wirelessly connected.



2.4 POINT-TO-MULTIPOINT OPERATION

A multipoint W-DMX system can support up to 512 individual receivers responding to a single W-DMX transmitter. All receivers in a multipoint system will listen only to the designated transmitter and they will all receive the full 512 channels of the DMX universe. This makes it straightforward to connect single fixtures or daisy-chained groups of fixtures to any of the receivers in the system.



1 PRODUCT SPECIFICATIONS

1.1 W-DMX products

The W-DMX system lies at the heart of every one of our products. The W-DMX radio card is specifically engineered by Wireless Solution Sweden AB to provide the same quality, reliability and performance as any hardwired DMX data link. In fact W-DMX gives you greater freedom to create reliable point-to-point and point-to-multipoint installations over large distances.

W-DMX is unique in its use of certain advanced radio techniques which are more often found in mobile phone and military communications. Rather than using fixed frequency channels, W-DMX uses adaptive frequency hopping technology to continually check for interference and to rapidly move operation over to clear radio channels. This occurs one thousand times every second and is used in combination with another advanced technique (called time division multiple access) which makes the most efficient use of every visited frequency channel.


The advantage of such technology will quickly become clear to you: consistent and wide ranging control of your lighting systems over potentially great distances. Indeed, you may actually find that it is all too easy to take W-DMX for granted, for two main reasons:

- Firstly, the complex communication protocols are fully auto-mated and concealed from view - you just plug-and-play, the units do all the hard work.
- Secondly, from the DMX connector of one unit to the DMX connector of another, the W-DMX system is totally transparent. W-DMX fully adheres to the USITT DMX-512 standard and can justifiably be called a 'wireless DMX cable'.

These are the reasons why in every independent comparison with competing products, W-DMX units continually take first prize for distance covered, resilience against interference and ease of installation.

1.2 PHYSICAL DIMENSIONS

1.2.1 DIMENSIONS: 204.5X196X174.5mm



1.2.2 WEIGHT: 0.53KG

2 INSTALLATION

2.1 Transmitter


- ◆1 Attach the antenna to the connector on the front panel. If using the standard antenna, use also the supplied adaptor.
- ◆2 Link the DMX source to the DMX insocket on the rear panel.
- ◆3 Connect power to the unit via the AC power input (90 to 250VAC).
- ◆4 If required, attach the supplied trussholder brackets to the topcover of the unit .

2.2 Receiver

- ◆1 Attach the antenna to the connector on the front panel. If using the standard antenna, use also the supplied adaptor.
- ◆2 Link the DMX source to the DMX insocket on the rear panel.
- ◆3 Connect power to the unit either via the AC power input (90 to 250VAC).
- ◆4 If required, attach the supplied trussholder brackets to the topcover of the unit .


<p>DMX Interface Transceivers on bus: 32 (max) Data rate: 250 kbps (max) ESD protection*: ±15 kV</p> <p>AC input 90-250VAC 50/60Hz 1A at 115VAC (max) 0.5A at 230VAC (max)</p> <p>Compliance declarations ETSI: EN300 328 & 300 826 EMC: EN301 489-17 CE: EN60950 FCC: UQT-WDXOEMPCBF IC: 6812A-WDMXOEM ARIB: 06215559/AA/00</p>	<p>RF characteristics Output power: 20 25** dBm 100 300** mW Frequency range: 2402 to 2479MHz Channel bandwidth: 1 Sensitivity at 0.1% BER: -95dBm * Slewrate limited for minimum of EMI in unterminated networks. ** Only in FCC output power mode.</p>
---	---

TRANSMITTER INTERFACE



<p>DMX Interface Transceivers on bus: 32 (max) Data rate: 250 kbps (max) ESD protection*: ±15 kV</p> <p>AC input 90-250VAC 50/60Hz 1A at 115VAC (max) 0.5A at 230VAC (max)</p> <p>Compliance declarations ETSI: EN300 328 & 300 826 EMC: EN301 489-17 CE: EN60950 FCC: UQT-WDXOEMPCBF IC: 6812A-WDMXOEM ARIB: 06215559/AA/00</p>	<p>RF characteristics Output power: 20 25** dBm 100 300** mW Frequency range: 2402 to 2479MHz Channel bandwidth: 1 Sensitivity at 0.1% BER: -95dBm * Slewrate limited for minimum of EMI in unterminated networks. ** Only in FCC output power mode.</p>
---	---

RECEIVER INTERFACE



2.1.1 To add receivers

Note: You can add receivers at any time, even during operation.


- ◆1 Power on the receiver unit(s) and ensure that they are not linked with any other transmitter (LINK indicators should be OFF).
- ◆2 On the transmitter unit, press and release the FUNCTION button. The transmitter will scan for all unlinked receivers for a period of ten seconds - the LINK indicator will flash rapidly.
- ◆3 If successful, each receiver's LINK indicator will go ON. If any failed, check that the receiver is in range and repeat procedure.

2.2.1 To link with a transmitter

- ◆1 Ensure that this receiver is not linked with any other transmitter (LINK indicator should be OFF).
- ◆2 On the transmitter unit, press and release the FUNCTION button. The transmitter will scan for all unlinked receivers for a period of ten seconds.
- ◆3 If successful, the receiver's LINK indicator will go ON. One or more Level indicators will then show the signal strength.

2.1.2 To unlink all receivers


- ◆1 On the transmitter, press and hold the FUNCTION button until LINK begins flashing. All registered receivers will be unlinked.



2

2.2.2 To unlink from a transmitter

- ◆1 On the receiver, press and hold the FUNCTION button until the LINK indicator goes OFF. The receiver is now unlinked.



3