





SCENA LED 200 CT

THE SUPER-BRIGHT THEATRE LED PROJECTOR WITH SELECTABLE COLOR TEMPERATURE

SCENA LED 200 CT is a **high power, compact, lightweight LED projector** suitable for TV studios, theatres, museums, exhibitions, events. **The unit LED's white color temperature is linearly tunable from 2700K to 6500K**; a must in the most demanding applications, where a perfectly adjustable white color temperature is a key requirement. SCENA LED 200 CT offers technical features that dramatically improve light quality and flexibility of use: **CRI > 90, 6.5°-70° linear zoom, flicker-free projection, DMX/RDM or manual control, noiseless operation, virtually zero maintenance costs, lower power consumption.**



03.TS051.46.F

MOTORIZED ZOOM VERSION AVAILABLE ON DEMAND

OUTPUT

- Single high-power white LED with linearly tunable color temperature (2700K - 6500K)
- CRI > 90
- LED lifespan: 50,000 hours (70% lumen output)

OPTICAL GROUP

- Ø 150 mm Fresnel lens
- 6.5°- 70° linear zoom

CONTROL

- DMX 512 / RDM
- 7 DMX channels (default) or 2 DMX channels
- 4-digit 7-segment LED display + 4 soft keys
- Internal operating system updatable via DTS dongle firmware uploader

POWER SUPPLY

- Full-range 100-240Vac 50-60 Hz
- Power consumption: 200 W max

- Power Factor: PF >0.94

CONNECTIONS

- Power supply: PowerCON TRUE1 In/Out panel connectors
- DMX: XLR 5-pole In/Out panel connectors

INTERNAL SAFETY DEVICES

Overvoltage and overtemperature circuits protection

OPERATING TEMPERATURE

-10° / 40° C

PHYSICAL

- IP20
- Weight: 8.4 Kg (18.5 lbs)
- Finishing: Black

SHIPPING

- Packaging: Carton box
- Box size (LxHxD): 525 x 280 x 345 mm (20.7" x 11" x 13.6")
- Weight: 9.8 Kg (21.6 lbs)

ACCESSORIES INCLUDED

- 1 x PowerCON TRUE1 female cable connector (code 0520P066)
- 1 x XLR 5 pins female cable connector (code 0508B147)
- 1 x XLR 5 pins male cable connector (code 0508B148)
- 1 x Filterframe Black finishing - already installed on the projector (code 02M093278.46)

ACCESSORIES ON REQUEST

- Barndoor Black finishing (code 03.TBD04)
- "C" Clamp G60 - max. Load 50 Kg (code 0521A004)
- Safety cable - 0.3x60 cm - max. capacity load 60 Kg (code 0521A010)
- DTS dongle firmware uploader (code 03.LA.206)

PHOTOMETRIC DATA

| | mt 2 ft 6.56 | mt 4 ft 13.12 | mt 6 ft 19.68 | mt 8 ft 26.25 | mt 10 ft 32.81 | |
|--------------------------|-------------------|------------------|------------------|------------------|-------------------|-------|
| BEAM ANGLE 6.5° @ 50% | lux center (lx) | 25000 | 6250 | 2778 | 1563 | 1000 |
| | foot candles (fc) | 2323 | 581 | 258 | 145 | 93 |
| | diameter (cm) | 23 | 45 | 68 | 91 | 114 |
| | diameter (ft) | 0.75 | 1.49 | 2.24 | 2.98 | 3.73 |
| BEAM ANGLE 70° @ 10% | lux center (lx) | 1888 | 472 | 210 | 118 | 76 |
| | foot candles (fc) | 175 | 44 | 19 | 11 | 7 |
| | diameter (cm) | 280 | 560 | 840 | 1120 | 1400 |
| | diameter (ft) | 9.19 | 18.38 | 27.57 | 36.76 | 45.94 |