ACCLAIM LED FRESNEL





The Strand Acclaim LED Fresnel is a full color theatrical Fresnel wash fixture designed specifically for small to medium spaces. The Acclaim has set the standard in 500W/650W lighting for a generation, and this new LED version offers saturated stage color washes and dramatic highlighting capabilities thanks to the high quality, industry standard 4.75" front lens coupled with the engineering excellence that has set Strand apart for over a century.

A true theatrical Fresnel, the Acclaim LED Fresnel offers superior control and light quality to comparable PAR fixtures. The adjustable 10° to 40° zoom provides manual adjustment with minimal light scatter, and the even, soft-edged beam easily blends with adjacent fixtures without hard edges to soften with frost filters or hot spots to smooth out in the beam. To shape the beam, users can add an optional rotating fourleaf barndoor that mounts on the front of the fixture and rotates around the axis for the perfect angle. The Acclaim LED Fresnel is available in black or white.




ACCLAIM LED FRESNEL


FEATURES AND BENEFITS


- 500W/650W-equivalent LED Fresnel true Fresnel with superior control and light quality than comparable PAR fixtures
- **Built with the DNA of Strand -** cost-effective luminaire from the original name in theatrical lighting
- Integrated 10° to 50° manual zoom precise beam sizing with minimal light scatter
- Optional rotating 4-leaf barn doors shape the beam to focus light where you need it
- Custom LED light source and RGBL color mixing system consistent output and color mixing with the entire Acclaim LED Series
- Available in black or white the perfect body color for your application

LIMITED WARRANTY

Every Strand product is backed by a minimum 2-year limited warranty against manufacturing defects and workmanship. Refer to the Strand Limited Warranty Card available at www.strandlighting.com/global/support/warranty for more details.







ACCLAIM LED FRESNEL

OURCE					
Туре	LED				
Color	RGBL	RGBL			
Wattage	150W				
Frequency adjustment	500Hz to 4000	Hz (Default 1500Hz)			
PTICAL PERFORMANCE					
Output lumens, max	4500 (beam) 8500 (field)				
	7100K/RGBL (FULL ON)	5600K / RGBL	3200K / RGBL		
CRI (RA)	85	84	80		
TM30 Rf	81	81	82		
TM30 Rg	102	102	115		
CQS	80	79	71		
TLCI	80	79	74		
SEAM					
Lens size	125mm (4¾ in) PMMA micro fresnel				
Zoom range	10° to 50°	10° to 50°			
Zoom operation	Dual manual rot	Dual manual rotary control			
Accessory holder	Integrated dual rail holder				
Gel frame size	145mm x 145mm	145mm x 145mm (5¾ in. x 5¾ in.)			
OLOR					
Color mixing type	RGBL				
OOLING SYSTEM					
Туре	Forced air				
Fan control, default		Auto ramping (default) Continuous spin (on)			
	Standard*	42.6 dBa			
Fixture output modes	Studio*	37 dBa			
	Whisper*	33.2 dBa			
	*Maximum dBa l	evel @ 1m (Fan On); base	e level 21 dBa		
OWER					
Range	100-240 VAC				
Power connector	Twist lock black	and yellow; In + Thru			
Max wattage	170W				
Standby wattage	8.8W				
ATA					
Control protocols	DMX (RDM)				
Data connections	5-pin XLR In/Thru				

ACCLAIM LED FRESNEL

Control modes	8-bit - (8 channels) 16-bit - (11 channels)			
PHYSICALS				
Body color options	Black, white			
Yoke	Adjustable height			
ENVIRONMENT	°C	°F		
Operating temperature range	-10 to 40	14 to 104		
Ingress protection rating	IP20			
DIMENSIONS (H x W x D)	mm	in		
Fixture only	253 x 190 x 353	$10 \times 7\frac{1}{2} \times 13\frac{3}{4}$		
Fixture + yoke	356 x 251 x 353	$14 \times 9\frac{3}{4} \times 13\frac{3}{4}$		
WEIGHT	kg	lb		
Fixture only	5.8	12.78		
APPROBATION				
Listings	ETL (UL & CSA)CB/IECEE Scheme for CE-LVD, FCC, ICES, RCM, CE-EMC, UKCA, RoHS, ISO 9001			

ACCLAIM LED FRESNEL

PHOTOMETRIC DATA (CALIBRATION ON)

For full photometric reports, visit the <u>product page</u> on our website.

NARROW ZOOM

LED TYPE		CANDELA	FIELD LUMENS	BEAM LUMENS	CRI(RA)	
7100K / RGBL (ful	l on)	105,909	8,415	2,750	85	
3200K / RGBL		95,690	7,847	2,506	84	
5600K / RGBL		102,193	7,879	2,602	80	
7100K (FULL ON	7100K (FULL ON)					
	ft	10.0	15.0	20.0	30.0	
Throw Distance	m	3.0	4.6	6.1	9.1	
Field Diameter	ft	1.5	2.4	2.9	4.6	
Field Diameter	m	0.5	0.7	0.9	1.4	
Illuminance	fc	1059	432	255	115	
	lux	11,400	4,650	2740	1240	
3200K						
Throw Distance	ft	10.0	15.0	20.0	30.0	
I nrow Distance	m	3.0	4.6	6.1	9.1	
Field Diameter	ft	1.5	2.4	2.9	4.6	
	m	0.5	0.7	0.9	1.4	
Illuminance	fc	957	407	232	104	
	lux	10,300	4,380	2491	1119	
5600K						
Throw Distance	ft	10.0	15.0	20.0	30.0	
	m	3.0	4.6	6.1	9.1	
Field Diameter	ft	1.5	2.4	2.9	4.6	
	m	0.5	0.7	0.9	1.4	
Illuminance	fc	1022	435	247	111	
	lux	11,000	4,678	2660	1195	

ACCLAIM LED FRESNEL

MEDIUM ZOOM

LED TYPE		CANDELA	FIELD LUMENS	BEAM LUMENS	CRI(RA)	
7100K / RGBL (ful	l on)	28,800	8,415	3,921	85	
3200K / RGBL		28,707	7,847	3,763	84	
5600K / RGBL		27,035	7,879	3,704	80	
7100K (FULL ON)						
Thursday Distance	ft	10.0	15.0	20.0	30.0	
Throw Distance	m	3.0	4.6	6.1	9.1	
Field Diameter	ft	3.8	5.6	7.6	11.0	
	m	1.2	1.7	2.3	3.4	
Illuminance	fc	288	131	74	38	
	lux	3,100	1,410	795	404	
3200K						
Throw Distance	ft	10.0	15.0	20.0	30.0	
Inrow Distance	m	3.0	4.6	6.1	9.1	
Field Diameter	ft	3.8	5.6	7.6	11.0	
	m	1.2	1.7	2.3	3.4	
Illuminance	fc	287	122	69	31	
	lux	3,090	1,314	747	335	
5600K						
Throw Distance	ft	10.0	15.0	20.0	30.0	
Tillow Distance	m	3.0	4.6	6.1	9.1	
Field Diameter	ft	3.8	5.6	7.6	11.0	
	m	1.2	1.7	2.3	3.4	
Illuminance	fc	270	115	65	29	
	lux	2,910	1,237	703	316	

ACCLAIM LED FRESNEL

WIDE ZOOM

LED TYPE		CANDELA	FIELD LUMENS	BEAM LUMENS	CRI(RA)
7100K / RGBL (ful	l on)	7,730	8,415	4,404	85
3200K / RGBL		6,800	7,847	4,020	84
5600K / RGBL		7,135	7,879	4,077	80
FULL ON 7100K					
Thursday Distance	ft	10.0	15.0	20.0	30.0
Throw Distance	m	3.0	4.6	6.1	9.1
Field Diameter	ft	7.8	12.3	16.4	25.2
	m	2.4	3.8	5.0	7.7
Illuminance	fc	77	34	21	12
	lux	832	371	230	128
3200K					
Throw Distance	ft	10.0	15.0	20.0	30.0
Tillow Distance	m	3.0	4.6	6.1	9.1
Field Diameter	ft	7.8	12.3	16.4	25.2
	m	2.4	3.8	5.0	7.7
Illuminance	fc	68	29	69	31
	lux	732	311	747	335
5600K					
Throw Distance	ft	10.0	15.0	20.0	30.0
	m	3.0	4.6	6.1	9.1
Field Diameter	ft	7.8	12.3	16.4	25.2
	m	2.4	3.8	5.0	7.7
Illuminance	fc	71	30	69	31
	lux	768	326	747	335

ACCLAIM LED FRESNEL

PRODUCT NAME	ORDER CODE
Acclaim LED Fresnel with power connector, black body	64511-001
Acclaim LED Fresnel with power connector, white body*	64511-101
*white option by special order only	
ACCESSORIES	ORDER CODE
Acclaim LED Fresnel 4 leaf barndoor (Black)	64511-010
Acclaim LED Fresnel 4 leaf barndoor (White/Black)	64511-110