



270 W RGBW LED Wash Light · IP65



HIGHLIGHTS

- 27 × 10 W RGBW LEDs, 15,000 lm luminous flux (25°)
- Colour temperature 2,400–8,000 K, CRI ≥ 80
- Beam angles 8° / 15° / 25° / 45°
- IP65 – for indoor and outdoor use
- DMX512, wired RDM and W-DMX control
- Fanless convection cooling
- Seetronic IP65 power and XLR in/out connectors
- OLED display with 4 buttons, 3 dimmer curves

OPTICS

Light source	270 W RGBW LED (27 × 10 W)
Luminous flux	15,000 lm (25°)
Colour temperature	2,400 – 8,000 K
CRI	Ra ≥ 80
Beam angle	8° / 15° / 25° / 45°
Strobe	0 – 20 Hz
Dimmer	0 – 100 %, 3 dimmer curves

POWER

Power input	100 – 240 V AC, 50/60 Hz
Power consumption	280 W @ 230 V
Power factor	0.95 @ 230 V
Power linking	≤ 6 units in series @ 230 V
Operating temperature	–20 °C to +45 °C

PHOTOMETRIC DATA – FULL ON

Beam angle	@ 5 m	@ 10 m
8°	13,100 lx	3,360 lx
15°	9,550 lx	2,920 lx
25°	2,916 lx	742 lx
45°	640 lx	160 lx

ACCESSORIES

Included	EU IP65 power cord
Optional	Diffusion filters (20° / 30° / 40° / 10×60° / 30×60°), base bracket, barndoor

CONTROL

Control modes	DMX512 / wired RDM / W-DMX
DMX channels	4 / 7 / 8 CH
Display	OLED display, 4 buttons
LED refresh rate	600 Hz – 25 kHz, selectable
Signal connection	Seetronic IP65 XLR 3/5-pin in/out, ≤ 32 in series

PHYSICAL

Dimensions (L × W × H)	454 × 80 × 250 mm
Weight	6.7 kg
Protection rating	IP65
Housing	Die-cast aluminium, black
Cooling	Convection, fanless
Mounting	Floor standing, vertical or side hanging

DIMENSIONS (MM)

