tauCyc 300

270 W RGBW LED Wash Light · IP65



HIGHLIGHTS

- 27 × 10 W RGBW LEDs, 15,000 lm luminous flux
- Colour temperature 2,400–8,000 K, CRI ≥ 80
- 20° beam angle, optional 45° / 80° frost filters
- IP65 — for indoor and outdoor use
- DMX512, wired RDM and W-DMX control
- Fanless convection cooling
- Seetronic IP65 power and XLR in/out connectors
- OLED display with 4 buttons, 3 dimmer curves

OPTICS

Light source	**270 W RGBW LED (27 × 10 W)**
Luminous flux	**15,000 lm**
Colour temperature	**2,400 – 8,000 K**
CRI	**Ra ≥ 80**
Beam angle	**20° (45° / 80° with frost filter)**
Strobe	**0 – 20 Hz**
Dimmer	**0 – 100 %, 3 dimmer curves**

POWER

Power input	**100 – 240 V AC, 50/60 Hz**
Power consumption	**280 W @ 230 V**
Power factor	**0.95 @ 230 V**
Power linking	**≤ 6 units in series @ 230 V**
Operating temperature	**–20 °C to +45 °C**

ACCESSORIES

Included	**EU IP65 power cord**
Optional	**Frost filters (45° / 80°)**

CONTROL

Control modes	**DMX512 / wired RDM / W-DMX**
DMX channels	**4 / 7 / 8 CH**
Display	**OLED display, 4 buttons**
LED refresh rate	**600 Hz – 25 kHz, selectable**
Signal connection	**Seetronic IP65 XLR 5-pin in/out, ≤ 32 in series**

PHYSICAL

Dimensions (L × W × H)	**454 × 80 × 250 mm**
Weight	**6.7 kg**
Protection rating	**IP65**
Housing	**Die-cast aluminium, black**
Cooling	**Convection, fanless**
Mounting	**Floor standing, vertical or side hanging**

DIMENSIONS (MM)

